



**FEATURES**

- Fully self-contained, rapid response system on a detachable platform
- Generator options
- Climate controlled environment
- NSA approved electronics storage safe
- Integrated Hawk Series Mast (see page 20)
- Available in 3-person (shown), 2-person, and 1-person configurations

**COMMAND, CONTROL , COMMUNICATIONS  
AND TACTICAL SHELTER - (C3T SHELTER)**

**SPECIFICATIONS**

EXTENDED HEIGHT :	VARIES
MINIMUM HEIGHT :	110"
TOWER SECTIONS :	4
MAXIMUM PAYLOAD :	400 LBS
TWIST :	*
SWAY :	*
DEFLECTION :	*
TRANSPORT HEIGHT :	10' 5" (125")
TRANSPORT WIDTH :	8' 9" (105")
TRANSPORT LENGTH :	25' (300")
TRANSPORTABLE WEIGHT :	8,480 LBS
TONGUE WEIGHT :	1,000 LBS
DECK HEIGHT :	25"
NUMBER OF AXLES :	2
C-130 TRANSPORTABLE :	** YES
ERECTABLE WIND SPEED :	25 MPH
MAXIMUM SAIL AREA :	VARIES - SEE HAWK SERIES PAGE 20
TIME TO ELEVATE MAST/TOWER :	VARIES - SEE HAWK SERIES PAGE 20
TIME TO LOWER MAST/TOWER :	VARIES - SEE HAWK SERIES PAGE 20
TIME TO TILT/RAISE MAST/TOWER :	N/A
DEPLOYMENT TIME (PERSONS/MINUTES) :	1/20 MINS
DEPLOYED FOOTPRINT :	301" x 105"
TILT MECHANISM :	N/A

**OPTIONS AND ACCESSORIES**

- AUTO-DEPLOY, AUTO-ACQUIRE SATELLITE ANTENNA DISH SYSTEM (VSAT)
- INTEGRATION OF VOICE, VIDEO AND DATA MANAGEMENT
- PROCESSES CLASSIFIED AND UNCLASSIFIED DATA
- COMMUNICATIONS EQUIPMENT OPTIONS
- CAMERA OPTIONS
- SERVER OPTIONS
- BLACKOUT LIGHTS
- WEAPONS RACK

\* To Be Determined : Twist, Sway and Deflection may vary depending on the type of payload.

\*\* = C3 Shelter can be detached from trailer and deployed remotely by fixed or rotary wing aircraft. NOTE: All values shown are approximate.