



RMTU656MDPLGO

FEATURES

- * Rapid Deployment, Minimal Setup
- * No Earth Penetrations Required
- * Guyed to Outriggers / Trailer

SPECIFICATIONS

EXTENDED HEIGHT :	56'
MINIMUM HEIGHT :	25'
TOWER SECTIONS :	3 @ 21' EA
MAXIMUM PAYLOAD :	650 LBS
TWIST :	*
SWAY :	*
DEFLECTION :	*
TRANSPORT HEIGHT :	8' 6 3/4" (102.75")
TRANSPORT WIDTH :	8' 6" (102")
TRANSPORT LENGTH :	28' 11" (347")
TRANSPORTABLE WEIGHT :	10,260 LBS
TONGUE WEIGHT :	1,040 LBS
DECK HEIGHT :	24"
NUMBER OF AXLES :	2
C-130 TRANSPORTABLE :	YES
ERECTABLE WIND SPEED :	40 MPH
MAXIMUM SAIL AREA :	32 SQ FT
TIME TO ELEVATE MAST/TOWER :	6.5 MINS
TIME TO LOWER MAST/TOWER :	6.5 MINS
TIME TO TILT/RAISE MAST/TOWER :	2 MINS
DEPLOYMENT TIME (PERSONS/MINUTES) :	1 / 25 MINS
DEPLOYED FOOTPRINT :	37' x 34'
TILT MECHANISM :	2 HYDRAULIC RAMS

* To Be Determined : Twist, Sway and Deflection may vary depending on the type of payload.

NOTE: All values shown are approximate. Sensors shown in photo are optional equipment.