



## RMTUHS639MGBGO

### FEATURES

- \* ..... Rapid Deployment, Minimal Setup
- \* ..... No Earth Penetrations Required
- \* ..... Guyed to Outriggers / Trailer

### SPECIFICATIONS

EXTENDED HEIGHT :	38' 6"
MINIMUM HEIGHT :	8' 6"
TOWER SECTIONS :	7
MAXIMUM PAYLOAD :	400 LBS
TWIST :	*
SWAY :	*
DEFLECTION :	*
TRANSPORT HEIGHT :	6' 8" (80")
TRANSPORT WIDTH :	8' (96")
TRANSPORT LENGTH :	19' 3" (231")
TRANSPORTABLE WEIGHT :	4,800 LBS
DECK HEIGHT :	24"
NUMBER OF AXLES :	1
C-130 TRANSPORTABLE :	YES
ERECTABLE WIND SPEED :	25 MPH
MAXIMUM SAIL AREA :	17 SQ FT
TIME TO ELEVATE MAST/TOWER :	2 MINS
TIME TO LOWER MAST/TOWER :	2 MINS
TIME TO TILT/RAISE MAST/TOWER :	1 ½ MINS
DEPLOYMENT TIME (PERSONS/MINUTES) :	2 / 20 MINS
DEPLOYED FOOTPRINT :	32' X 26' 6"
TILT MECHANISM :	DOUBLE REDUCTION GEAR BOX

\* To Be Determined : Twist, Sway and Deflection may vary depending on the type of payload.

NOTE: All values shown are approximate.